

ResiTHERM® 37 Accessories

Core bit for perforated brick BST

Drilling aid for core bit ABH



Core bit BST and drilling aid ABH for core bit for ResiTHERM®

Type	Art-No	d [mm]	L [mm]	Connecting thread	€/pc	[pcs]	[pcs]
BST 39 x 220	39220BST	39	220	M16		1	–
ABH	39ABH	35	60	–		1	–

AD 100

AD 200



Adapter shank AD hexagon for core bit BST for ResiTHERM®

Type	Art-No	L [mm]	Connecting thread	Shank for drilling machine	Insulation thickness [mm]	€/pc	[pcs]	[pcs]
AD 100	100M16AD	100	M16	hexagon	≤ 160		1	–
AD 200	200M16AD	200	M16	hexagon	160 - 260		1	–



Vinylester VYSF (styrene free)

European Technical Assessment
Option 1 for cracked concrete
(M8 – M30, Ø8 – Ø32)European Technical Assessment
for masonry
(M8 - M16)

see assessment



Type	Art-No	Content [ml]	Mixings nozzles included [pcs]	€/pc	[pcs]
VY 300 SF	300VSF	280	2		12

Curing times see page 178



StickFX Professional adhesive and sealant CL

Type	Art-No	Content [ml]	Colour	Description	€/pc	[pcs]
CL	TR290MSCL	290	transparent	Adhesive and sealant		12



Distance washer AS Polyamid, DIN 9021 for M12

Type	Art-No	Outer Ø [mm]	Disc hole Ø [mm]	Height H [mm]	€/100 pcs	[pcs]	[pcs]
AS	129021AS	37	13	3		50	–

To use as a distance washer for relining (if needed).



APVM

Manual dispenser APVM

Type	Art-No	Suitable for ResiFIX Type	€/100 pc	[pcs]
APVM	345APVM	345 / 300 / 280 / 165		1

Manual dispenser APVM is recommended to read the scale units of ResiFIX VY (outer rod serves as a pointer).



Blow out pump AB

Type	Art-No	Tube-Ø [mm]	€/pc	[pcs]	[pcs]
AB	BOP	8		1	–

